KERN **TGC 150-2**



0,2%

Slim pocket balance with large stainless steel weighing plate and practical tare pan

Tolerance (% of [Max])



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	Pocket balance
Product family	TGC

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	150 g
Weighing capacity [Max] (ct)	750 ct
Readability [d]	0,01 g
Readability carat [d] (ct)	0,05 ct
Resolution	15.000
Linearity	± 0,3 g
Reproducibility	0,2 g
Tare range	150 g
Default unit	g
Units	g gn dwt ozt ct
Adjustment options	Adjusting with external weight
Recommended adjusting weight	50 g (M2); 100 g (M2)
Possible calibration points	50 g; 60 g
Stabilization time	2 s
Warm-up time	30 min
Eccentric loading at 1/3 [Max]	0,3 g
Maximum creep (15 minutes)	40 mg
Maximum creep (30 minutes)	80 mg

Tolerance (% or [wax])	0,2%
Approval	
CE mark	✓
Display	
Display type	LCD
Display backlight	✓
Display digit height	12 mm
Languages of the user interface	Symbol language
Construction	
Dimension housing (W×D×H)	100×130×18 mm
Material display housing	Plastics
Material housing	plastic
Material weighing plate	stainless steel
Dimensions weighing surface (Ø)	81 mm
Functions	
Number of keys for operation	4
Auto-off interval(s) in battery	4 min
mode/rechargeable battery mode	17 10
Tare function	manual (multi)
IP protection - complete device	=
Power Supply	
	Battery
Power Supply	Battery 2×CR2032
Power Supply Supplied power supply	•
Power Supply Supplied power supply Battery	2×CR2032
Power Supply Supplied power supply Battery Battery / accumulator type	2×CR2032 Li-Metal
Power Supply Supplied power supply Battery Battery / accumulator type Battery connection	2×CR2032 Li-Metal Pad + Spring
Power Supply Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity	2×CR2032 Li-Metal Pad + Spring 210 mAh
Power Supply Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h
Power Supply Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h
Power Supply Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h
Power Supply Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h
Power Supply Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min]	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h 22 h
Power Supply Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min] Humity of environment [Max]	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h 22 h
Power Supply Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min]	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h 22 h
Power Supply Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min]	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h 22 h 80 % 90 % 0 °C 40 °C
Power Supply Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min] Storage temperature [Min]	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h 22 h 80 % 90 % 0 °C 40 °C -20 °C
Power Supply Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Min] Storage temperature [Min]	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h 22 h 80 % 90 % 0 °C 40 °C -20 °C

KERN **TGC 150-2**



Slim pocket balance with large stainless steel weighing plate and practical tare pan

Dimensions packaging (W×D×H)	142×195×30 mm
Net weight	0,152 kg
Shipping method	Parcel service
Net weight approx.	0,20 kg
Gross weight approx.	0,25 kg
Shipping weight	0,209 kg

Services (optional)	
Article number for adjustment at the location of installation	961-247
Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD









OPTION

