KERN TGD 50-3CS05



Compact pocket carat balance for precision weighing of jewellery and precious stones



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	Pocket balance
Product family	TGD

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	50 g
Weighing capacity [Max] (ct)	250 ct
Readability [d]	0,001 g
Readability carat [d] (ct)	0,005 ct
Resolution	50.000
Linearity	± 0,003 g
Reproducibility	0,003 g
Tare range	50 g
Default unit	g
Units	g gn dwt ozt ct oz
Adjustment options	Adjusting with external weight
Recommended adjusting weight	50 g (F2)
Possible calibration points	50 g
Stabilization time	3 s
Warm-up time	30 min
Eccentric loading at 1/3 [Max]	0,005 g
Maximum creep (15 minutes)	4 mg
Maximum creep (30 minutes)	8 mg

Approval	
CE mark	✓
Display	
Display type	LCD touch
Display backlight	✓
Display digit height	20 mm
Languages of the user interface	Symbol language
Construction	
Dimension housing (W×D×H)	96×150×64 mm
Material display housing	Plastics
Material housing	plastic
Material weighing plate	stainless steel
Material platform	Plastics
Material draught shield	plastic
Dimensions weighing surface (Ø)	65 mm
Levelling feet adjustable	✓
Functions	
Number of keys for operation	4
Auto-off interval(s) in battery mode/rechargeable battery mode	5 min
Tare function	manual (multi)
IP protection - complete device	-
Power Supply	
Power Supply Supplied power supply	Power supply & battery included
Supplied power supply	included
Supplied power supply Battery	included 4×1.5 V AAA
Supplied power supply Battery Battery / accumulator type	included 4×1.5 V AAA Alkali(-Manganese)
Supplied power supply Battery Battery / accumulator type Battery connection	included 4×1.5 V AAA Alkali(-Manganese) Pad + Spring
Supplied power supply Battery Battery / accumulator type Battery connection Battery operating time	included 4×1.5 V AAA Alkali(-Manganese) Pad + Spring
Supplied power supply Battery Battery / accumulator type Battery connection Battery operating time Environmental conditions	included 4×1.5 V AAA Alkali(-Manganese) Pad + Spring 150 h
Supplied power supply Battery Battery / accumulator type Battery connection Battery operating time Environmental conditions Humity of environment [Min]	included 4×1.5 V AAA Alkali(-Manganese) Pad + Spring 150 h
Supplied power supply Battery Battery / accumulator type Battery connection Battery operating time Environmental conditions Humity of environment [Min] Humity of environment [Max]	included 4×1.5 V AAA Alkali(-Manganese) Pad + Spring 150 h 15 % 80 %
Supplied power supply Battery Battery / accumulator type Battery connection Battery operating time Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min]	included 4×1.5 V AAA Alkali(-Manganese) Pad + Spring 150 h 15 % 80 % 5 °C
Supplied power supply Battery Battery / accumulator type Battery connection Battery operating time Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max]	included 4×1.5 V AAA Alkali(-Manganese) Pad + Spring 150 h 15 % 80 % 5 °C
Supplied power supply Battery Battery / accumulator type Battery connection Battery operating time Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max] Packing & Shipping	included 4×1.5 V AAA Alkali(-Manganese) Pad + Spring 150 h 15 % 80 % 5 °C 35 °C
Supplied power supply Battery Battery / accumulator type Battery connection Battery operating time Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max] Packing & Shipping Readability force [d] (N)	included 4×1.5 V AAA Alkali(-Manganese) Pad + Spring 150 h 15 % 80 % 5 °C 35 °C
Supplied power supply Battery Battery / accumulator type Battery connection Battery operating time Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max] Packing & Shipping Readability force [d] (N) Net weight	included 4×1.5 V AAA Alkali(-Manganese) Pad + Spring 150 h 15 % 80 % 5 °C 35 °C 1 d 1,025 kg
Supplied power supply Battery Battery / accumulator type Battery connection Battery operating time Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Max] Packing & Shipping Readability force [d] (N) Net weight Shipping method	included 4×1.5 V AAA Alkali(-Manganese) Pad + Spring 150 h 15 % 80 % 5 °C 35 °C 1 d 1,025 kg Parcel service

1

KERN TGD 50-3CS05



Compact pocket carat balance for precision weighing of jewellery and precious stones

Shipping weight 1,905 kg

Services (optional)	
Article number for adjustment at the location of installation	961-247\$05
Article number for DAkkS calibration	963-127805.
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD











OPTION

